

# SAFETY DATA SHEET

Conforms to OSHA HazCom 2012, CPR, NOM-018-STPS-2000 Standards & GHS

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**Product Name(s):** PVL Limestone

**Product Identities:** Limestone, Limestone Flour, Calcium Carbonate

**Supplier/Manufacture:**

Diversified Minerals Inc.  
1135 E. Wooley Road  
Oxnard CA, 93030  
(888) 364-9595

**Recommended Uses:** Absorbent, Mineral Filler

**Poison Control System:**  
**(800) 222-1222**

**Restrictions on Use:** Strong Acids, Fluorine and Strong Oxidizing Agents

## SECTION 2: HAZARD IDENTIFICATION

	<b>WARNING</b>		
	<p>Irritant: Causes eye, skin and inhalation irritation</p> <p>Use proper engineering controls, work practices, and personal protective equipment to prevent exposure to wet or dry product.</p> <p>Read SDS for details.</p>	<p>Respiratory Protection</p>	<p>Eye Protection</p>

**GHS Classification:**

- Acute Toxicity Oral - Category 4
- Skin Corrosion/Irritation - Category 2
- Eye Damage/Irritation - Category 2B
- Carcinogenicity - Category 1A
- Specific Target Organ Toxicity Repeat Exposure - Category 1

**GHS LABEL ELEMENTS Symbol(s)**



### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

CAS #	Component	Percent
1317-65-3	Limestone	92
14808-60-7	Quartz	5
1309-37-1	Iron Oxide	1
1309-48-4	Magnesium oxide	1
1344-28-1	Aluminum Oxide	1

PVL Limestone is made sintered and ground earth materials. Trace amounts of chemicals may be detected due to the naturally variable chemical compositions of earth materials.

### **SECTION 4: FIRST-AID MEASURES**

- Eye Contact:** Rinse eyes thoroughly with water for at least 15 minutes, including under lids to remove all particles. Seek medical attention for discomfort or if irritation or other symptoms do not subside.
- Skin Contact:** Wash with cool water and pH neutral soap or a mild skin detergent. Seek medical attention for rash, irritation, dermatitis and prolonged unprotected exposures to wet PVL Limestone.
- Inhalation:** Move person to fresh air. Seek medical attention for discomfort or if coughing or other symptoms do not subside.
- Ingestion:** Do not induce vomiting. If conscious, have person drink plenty of water. Seek medical attention or contact poison control immediately.

### **SECTION 5: FIRE-FIGHTING MEASURES**

- General Hazard:** Avoid breathing dust..
- Extinguishing Media:** Use extinguishing media appropriate for surrounding fire.
- Firefighting Equipment:** PVL Limestone poses no fire-related hazard.
- Combustion Products:** In excess of 1000°C compounds will break down into their constituent oxides.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

- General:** Place spilled material into a container. Avoid actions that cause the PVL Limestone to become airborne. Avoid inhalation of PVL Limestone and contact with skin. Wear appropriate Personal Protective Equipment (PPE) as described in Section 8 below. Scrape wet PVL Limestone into a container. Allow material to dry or solidify before disposal. Do not wash PVL Limestone down sewage and drainage systems or into bodies of water (e.g. streams).
- Waste Disposal:** Dispose of PVL Limestone according to Federal, State, Provincial and local regulations.

## SECTION 7: HANDLING AND STORAGE

<b>General:</b>	<p>Keep dry until used. Keep bulk and bagged PVL Limestone dry until used. Stack bagged material in a secure manner to prevent falling. Bagged PVL Limestone is heavy and poses risks such as sprains and strains to the back, arms, shoulders and legs during lifting and mixing. Handle with care and use appropriate control measures.</p> <p>Properly ground all pneumatic conveyance systems. The potential exists for static build-up and static discharge when moving PVL Limestone powders through a plastic, non-conductive, or non-grounded pneumatic conveyance system. The static discharge may result in damage to equipment and injury to workers.</p>
<b>Engulfment hazard:</b>	To prevent burial or suffocation, do not enter a confined space, such as a silo, bin, bulk truck or other storage container or vessel that stores or contains PVL Limestone. PVL Limestone can build up or adhere to the walls of a confined space. The PVL Limestone can suddenly release, collapse, or fall unexpectedly.
<b>Housekeeping:</b>	Avoid actions that cause PVL Limestone to become airborne during clean-up such as dry sweeping or using compressed air. Use HEPA vacuum or thoroughly wet with water to clean-up dust. Use PPE described in Section 8 below.
<b>Storage Temperature:</b>	-32°C – 100°C
<b>Storage Pressure:</b>	Ambient Pressure
<b>Storage Moisture:</b>	Keep dry.
<b>Clothing:</b>	Promptly remove and launder clothing that is dusty or wet with PVL Limestone. Thoroughly wash skin after exposure to PVL Limestone.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Engineering Controls:</b>	Use local exhaust and general dilution ventilation or other suppression methods to maintain dust levels below exposure limits.
<b>Personal Protective Equipment (PPE):</b>	
<u>Respiratory Protection:</u>	Under ordinary circumstances no respiratory protection is required. Wear a NIOSH approved respirator that is properly fitted and is in good condition when exposed to dust above exposure limits.
<u>Eye Protection:</u>	Wear ANSI approved glasses or safety goggles when handling dust or wet PVL Limestone to prevent contact with eyes. Wearing contact lenses when using PVL Limestone, under dusty conditions, is not recommended.
<u>Skin protection:</u>	Wear gloves, boot covers and protective clothing impervious to water to prevent skin contact. Do not rely on barrier creams, in place of impervious gloves. Remove clothing and PPE that become saturated with wet PVL Limestone and immediately wash exposed areas.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical State:</b>	Solid (powder)	<b>Evaporation Rate:</b>	NA
<b>Appearance:</b>	Pale Yellow granular	<b>pH (in water):</b>	7-9
<b>Odor:</b>	None	<b>Boiling Point:</b>	>1000°C
<b>Vapor Pressure:</b>	NA	<b>Freezing Point:</b>	None, solid
<b>Vapor Density:</b>	NA	<b>Viscosity:</b>	None, solid
<b>Specific Gravity</b>	1.72	<b>Solubility in water:</b>	Negligible

## **SECTION 10: STABILITY AND REACTIVITY**

- Stability:** Stable. Keep dry until use. These products may react with water, resulting in a slight release of heat, depending upon the amount of lime (Calcium oxide) present. Avoid contact with incompatible materials.
- Incompatibility:** PVL Limestone is incompatible with acids. PVL Limestone reacts violently with acids to produce heat.
- Hazardous Polymerization:** None.
- Hazardous Decompositions:** Will not spontaneously occur. Avoid exposure to acids. Product exposed directly to acids may release hydrogen sulfide. Hydrogen sulfide is a hazardous, toxic and poisonous gas.

## **SECTION 11 AND 12: TOXICOLOGICAL AND ECOLOGICAL INFORMATION**

For questions regarding toxicological and ecological information refer to contact information in Section 1.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

Dispose of waste and containers in compliance with Federal, State, Provincial and Local regulations.

## **SECTION 14: TRANSPORT INFORMATION**

This product is not classified as a Hazardous material under US D.O.T or Canadian TDG regulations.

## **SECTION 15: REGULATORY INFORMATION**

**OSHA/MSHA Hazard Communication:**

This product is considered by OSHA/MSHA to be a hazardous chemical and should be included in the employer's hazard communication program.

**CERCLA/Superfund:**

This product is not listed as a CERCLA hazardous substance.

**EPCRA  
SARA Title III:**

This product has been reviewed according to the EPA Hazard Categories promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 and is considered a "hazardous substance" a delayed health hazard.

**EPCRA  
SARA Section 313:**

This product does not contain any of the substance subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372

**California Proposition 65:**

WARNING: This material may contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

## SECTION 16: OTHER INFORMATION

### General Abbreviations:

>	Greater than	NIOSH	National Institute for Occupational Safety and Health
<	Lesser than	NTP	National Toxicology Program
ACGIH	American Conference of Governmental Industrial Hygienists	OSHA	Occupational Safety and Health Administration
CAS RN	Chemical Abstracts Reference Number	PEL	Permissible Exposure Limit
CERCLA	Comprehensive Environmental Response, Compensations and Liability Act	pH	Negative log of hydrogen ion
CFR	Code of Federal Regulations	PPE	Personal Protective Equipment
CL	Ceiling Limit	R	Respirable Particulate
DOT	Department of Transportation	RCRA	Resource Conservation and Reauthorization Act
g/cm <sup>3</sup>	Grams per cubic centimeter	SARA	Superfund Amendments and Reauthorization Act
HEPA	High-Efficiency Particulate Air	SDS	Safety Data Sheet
HMIS	Hazardous Materials Identification Systems	T	Total Particulate
IARC	International Agency for Research on Cancer	TDG	Transportation of Dangerous Goods
mg/m <sup>3</sup>	Milligrams per cubic meter	TLV	Threshold Limit Value
MSHA	Mine Safety and Health Administration	TWA	Time Weighted Average (8 hour)
NA	Not Applicable	WHMIS	Workplace Hazardous Materials Information System
NFPA	National Fire Protection Association	---	-----

This SDS (Section 1-16) was revised on July 10, 2015.

An electronic version of this SDS is available at: [www.dmicement.com](http://www.dmicement.com)

The data in the Safety Data Sheet related only to the specific material designated herein and does not relate to use in combination with any other material on or in any process. Diversified Minerals Inc. (DMI) believes the information contained herein is accurate; however, DMI makes no guarantees with respect to such accuracy and assumes no liability in connection with the use of the information contained herein which is not intended to be and should not be construed as legal advice or as insuring compliance with any federal, state or local laws or regulations. Any party using this product should review all such laws, rules, or regulations prior to use, including but not limited to Federal, Provincial, State and Local regulations.

NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OTHERWISE.