

Technical Data Sheet

Fly Ash—Class F

Per ASTM C-618 Specifications

Product Description: Fly Ash is a pozzolanic cement replacement that enhances the performance of concrete by increasing compressive strength, improving workability, durability, long term strength, resistance to freeze-thaw damage and reduces permeability, efflorescence shrinkage, thermal cracking, alkali silica reaction and sulfate attack in concrete. Basically using fly ash makes better concrete that is more economical and better for the environment.

Physical Properties:

pH Value	4-12
Retained on a 325 Sieve	26.6%
Specific Gravity	2.0-2.9
Bulk Density	154.2 pcf

Chemical Composition:

Quartz	SiO ₂	59.9
Calcium Oxide	CaO	11.5
Iron Oxide	Fe ₂ O ₃	4.8
Aluminum Oxide	Al ₂ O ₃	14.3
Sulfur Trioxide	SO ₃	1.1
Sodium Oxide	Na ₂ O	0.6
Potassium Oxide	K ₂ O	0.4
Moisture Content		0.2
LOI		2.4

Available Packaging:

Bulk, Super Sacks, Paper Bags. DMI can also provide on-site storage.

The data in the Technical Data Sheet related only to the specific material designated herein and does not relate to use in combination with any other material on or in any process. Diversified Minerals Inc. (DMI) believes the information contained herein is accurate; however, DMI makes no guarantees with respect to such accuracy and assumes no liability in connection with the use of the information contained herein which is not intended to be and should not be construed as legal advice or as insuring compliance with any federal, state or local laws or regulations. Any party using this product should review all such laws, rules, or regulations prior to use, including but not limited to Federal, Provincial, State and Local regulations.

NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OTHERWISE.